

## R603 STONE SEAL

### LABEL INSTRUCTIONS

#### Product Description & Directions for Use:

Durable water and oil resistant penetrating sealer for concrete, brick, grout, terracotta, limestone, sandstone, decorative tiling and other porous or mineral floors and surfaces. Stone Seal provides an invisible protective barrier against oil and water on porous stone surfaces. Stone Seal can be used on internal and external stone floors, subject to testing.

#### For professional and industrial use only.

Stone Seal is ready-to-use. Do not dilute further. Coverage is approximately 150 to 200m<sup>2</sup> per 5 litres, depending upon porosity of floor.

Always pre-test surface to be treated before proceeding and allow treatment to dry fully before testing and assessing suitability for full application.

Apply Stone Seal solution by roller, mop or saturated soft brush.

#### Do not apply by spray.

For indoor use ensure there is adequate ventilation.

Allow surface to dry completely before use.

**Do not allow product to freeze. Rinse application equipment in water.**

- Water-based oil & water resistant sealer for concrete, stone, terracotta, brick and other mineral & porous flooring surfaces.
- Does not change the appearance of natural stone.
- Apply by brush, roller or mop.
- Clear liquid with mild acrylic odour.

**pH Concentrate:** 5.0

**pH Diluted:** Not applicable

### HANDLING AND SAFETY

Keep out of reach of children.

Do not breathe vapour / spray.

Do not get in eyes, on skin, or on clothing.

Wear protective gloves / protective clothing / eye protection / face protection.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.

Continue rinsing. Get medical advice / attention.

Safety data sheet available on request.

Please consult the Safety Data Sheet before using this product.

This product is intended for professional use only. The information given is intended to be of assistance to users but is without guarantee. Variations can occur in application and users are advised to conduct their own tests. Suggestions for use neither give nor imply any guarantee as to the intended use.

**Product Name:** STONE SEAL      **Product Code:** R603

**Manufacturer:** Prochem Europe Ltd., Oakcroft Road, Chessington, Surrey KT9 1RH, UK.

Telephone No: 020 8974 1515 (UK) +44 20 8974 1515

Website: [www.prochem.co.uk](http://www.prochem.co.uk) Email: [sales@prochem.co.uk](mailto:sales@prochem.co.uk)

